




96-D Allen Boulevard
 Farmingdale, New York 11735-5626 USA
 Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
 e-mail: testing@govmark.com

Received:08/04/2016	Completed:08/08/2016	Letter: Z	BG	P.O.#:	Test Report #:	3-14673-0-
Client's Identification	Style: Silver Screen.. Composition: 64% PVC. 36% Fiberglass. Weight: 11.8 oz/y ² . Thickness: 0.02". End Use: Interior Roller Shades.					
Tested For: Jessica Bondell	Key Test: CA 1237 Sm					195
Rollease Acmeda, Inc. 200 Harvard Avenue Stamford, CT 06902			Tel: 1-(203)-964-1573		Ext:	
			Fax: 1-()- -			
LE: 1993; V 09/15 NTR 04/16 PC: 1H /jd SM/mg						
TEST PERFORMED: California Fire Marshal Title 19: Section 1237 (Proposed Revision 8/9/93) Fire Resistance; Small Scale Test - INTERIOR MATERIALS QUALIFICATION						
RESULTS REPORTED: <input checked="" type="checkbox"/> Initially <input type="checkbox"/> After 3 dry cleanings <input type="checkbox"/> After 5 launderings @ 160°F						
RESULTS:	Specimen #	Afterflame (seconds)	Afterglow (seconds)	Char Length (inches)		
	-----			-----		
Warp:	1	0	0	2.6		
	2	0	0	3.3		
	3	0	0	3.3		
	4	0	0	3.6		
	5	0	0	3.2		

	Avg:	0				
Fill:	6	0	0	3.1		
	7	0	0	2.8		
	8	0	0	3.4		
	9	0	0	3.4		
	10	0	0	3.0		

	Avg:	0				
APPROXIMATE WEIGHT OF MATERIAL (as measured by Govmark): 11.3 oz/yd ²						
ACCEPTANCE CRITERIA:						
Afterflame:	4.0 seconds maximum average for warp or fill					
Afterglow:	(see Note #2 below)					
Char Length:	6.0 inches maximum for any individual specimen					
NOTES:						
1. An asterisk (*) next to any char length measurement indicates that a part of the char length is melt away due to heat from the flame source and not from propagating flame. Therefore, the sample submitted meets the requirements of Title 19 - California Code of Regulations, Section 1237 and 1237.1 for materials weighing less than 4 oz/yd ² .						
2. Afterglow is required to be reported; however, it is not factored into the Acceptance Criteria.						
(Page 1 of 2)						

File Conv



96-D Allen Boulevard
 Farmingdale, New York 11735-5626 USA
 Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
 e-mail: testing@govmark.com

Page 2

Received:08/04/2016	Completed:08/08/2016	Letter: Z	BG	P.O.#:	Test Report #:	3-14673-0-
Client's Identification	Style: Silver Screen.. Composition: 64% PVC. 36% Fiberglass. Weight: 11.8 oz/y ² . Thickness: 0.02". End Use: Interior Roller Shades.					
Tested For: Jessica Bondell	Key Test: CA 1237 Sm				195	
Rollease Acmeda, Inc. 200 Harvard Avenue Stamford, CT 06902		Tel: 1-(203)-964-1573		Ext:		
		Fax: 1-()- -				

CONCLUSION: Based on the above Results and Acceptance Criteria, the item tested:

Complies; Does not comply

REMARKS: None.

NOTE: The number of test specimens and Acceptance Criteria are based on a proposed revision issued and implemented by the California State Fire Marshal in August 1993. In substance, the following has occurred:

1. A maximum afterflame of 4 seconds is permitted as opposed to 1 second.
2. It was clarified that the char length maximum of 6 inches applies to any individual specimen and is not an average requirement.
3. Ten specimens are tested in lieu of 6 specimens.

This report issues the conclusion to Section 1237 based on the California State Fire Marshal's continued endorsement of the proposed revision.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

 AUTHORIZED SIGNATURE
 GOVMARK
 /pm /mo

Robert I. Brown

(Page 2 of 2)

AUG 08 2016

The results contained in this report relate only to item(s) tested. The test report shall not be reproduced, except in full, without written approval from Govmark.

File Copy